

EMC/485/2021-CRU2 (ADM)

04/02/2022

NOTICE INVITING QUOTATION

Sub:- Inviting quotation for Refilling of 2 No and Purchase of 2 No of Fire extinguisher in Energy Management Centre -Kerala - reg

Competitive quotations are invited for Refilling of 2 No & purchase of 2 No of fire extinguishers in Green Building of Energy Management Centre-Kerala.

Sl.No	Particulars	Rate Rs. Incl. GST	Quantity	Total Rs. Incl. GST	Remarks
1	<p>Water mist 2L Fire Extinguisher: WATERMIST 2L Fire Extinguisher, Stored Pressure Type, Pressure Gauge, Gross Weight : 4.6 Kg, Empty Weight : 2.6 Kg, Can Height : 485 MM, Diameter : 180MM, Discharge time Minimum: 13 Sec, Range minimum : 4 Meters, Applicable on Class-A, Class-F and Electrically Started Fires, RATING-25F, Can Construction: Deep drawn & Mig welded, Valve Construction: Forging & Machining, Internal Coating of Can: Epoxy Powder coating, External Coating of Can: Epoxy Polyster Powder coating, Sheet metal thickness: 1.5MM,</p> <p>Helium Leak Detection Tested, ISI and CE Approved. Confirms to IS: 15683.</p> <p>3 Years Warranty</p>		01		Refill

2	<p>HCFC123 Clean Agent 2kg Fire Extinguisher : Clean Agent HCFC123 2kg Fire Extinguisher, Stored Pressure Type, Gross Weight: 3.7 Kg, Empty Weight: 1.7 Kg, Can Height: 344MM, Diameter: 108MM, Discharge time Minimum : 13 Sec, Controllable discharge mechanism, Range minimum 4 Meters, Applicable on Class A,B, C and electrically started Fire, A Rating-1A B Rating 8B, Can Construction : Deep Drawn & CO2 Mig welded, Valve Construction : Forging & Machining, Internal Coating of Can : Epoxy Powder coating, External Coating of Can : Epoxy Polyester Powder coating, Sheet metal thickness : 1.60MM, Helium Leak Detection Tested, ISI & CE Approved. 3 Years Warranty</p>		01	Refill
3	<p>MAP 90 ABC Fire Extinguisher-6 KG: Mono Ammonium Phosphate Powder 90, 6 Kg Fire Extinguisher, Stored Pressure Type, Pressure Gauge, Gross Weight 9.4 Kg, Empty Weight : 3.4 Kg, Can Height:- 480MM, Diameter : 160MM, Discharge time minimum : 13 Seconds ,Controllable discharge mechanism, Range minimum : 4 Meters, Applicable on Class A,B,C and electrically started Fire, A Rating- 6A, B Rating183B, Can Construction : Deep drawn & CO2Mig welded,</p>		02	Purchase

Valve Construction : Forging & Machining, Internal Coating of Can : Epoxy Powder coating, External Coating of Can - Epoxy Polyster Powder coating, Sheet metal thickness : 1.60MM, Helium Leak Detection Tested, ISI ,CE,LPCB, KITE and PED Approved. 6 Years Warranty.				
Total Amount Rs. (Inclusive of GST)				
Total amount in words:				

The envelope containing the quotation, with all taxes and duties and others terms and conditions, should bear the superscription " **Bid for supply of Fire Extinguishers in Green Building of Energy Management Centre-Kerala** " and should be addressed to **Director, Energy management Centre, Sreekrishna Nagar, Sreekariyam, Thiruvananthapuram-17**

Last date of receipt of quotation is 4.00 pm on 15/02/2022

Terms and conditions

- Shall provide brochures or catalogs of items along with quotes.
- Items should be supplied and installed at Energy management Centre Green Building.
- Payment Terms: The 95% of total cost will be released against invoice after supply and installation of items and rest 5% after one year.



Director